

Submittal Data

Flex-Lite Series

Storage Tanks

Job Name: _____ Schedule #: _____
 Location: _____ Model #: _____
 Engineer: _____ Representative: _____
 Contractor: _____

Description

Light commercial and residential storage, contact, and hydro-pneumatic composite pressure vessel. High strength precision molded internal liner reinforced with continuous strand fiberglass and sealed with high grade epoxy resin. High temperature glass reinforced connections for extended outdoor exposure applications. Lightweight, non-corrosive construction for maximum life and maximum flexibility.



Materials of Construction

Shell: Chemically coupled polypropylene
 Connection: Bottom 1 1/4" Male socket, Rigid PVC
 Side & Top 1 1/4" Female NPT, Glass reinforced polypropylene

Ratings

Max. Working Pressure 100 PSI
 Max. Working Temperature 120° F

Model	Capacity (Gal. / Liter)	Diameter (Inch/cm)	Height (Inch/cm)	Bottom Connection Height (Inch/cm)
FLS-40	40 / 151	16 / 41	53.5 / 136	1.75 / 4.4
FLS-80	80 / 303	21 / 53	62.75 / 159	1.75 / 4.4
FLS-120	120 / 454	24 / 61	71.5 / 181	2.25 / 5.7



300 Pond St
 Randolph, MA

781.986.2424
 Fax 781.986.2029

www.flexconind.com