



Jet-Rite 2 Series - Inline Models

Model #s	Diameter		Dimensions Height/Length		System Connect.	Volume		Shipping (Box) Volume		Shipping (Box) Weight	
	in.	cm.	in.	cm.		gal.	liter	cu. ft.	cu. m.	lbs.	kilos
PJR-6	8.0	20	12.0	30	3/4"	2.1	8	0.50	0.02	5.0	2.3
PJR-15	11.0	28	14.5	37	3/4"	4.8	18	1.10	0.03	10.0	4.6
PJR-25	12.5	32	20.0	51	3/4"	8.5	32	2.50	0.07	13.0	6.9
PJR-44IL	15.3	39	19.75	50	1"	14.0	53	3.03	0.09	23.3	10.6

Jet-Rite 2 Series - Horizontal Models

Model #s	Diameter		Dimensions Height/Length		System Connect.	Volume		Shipping (Box) Volume		Shipping (Box) Weight	
	in.	cm.	in.	cm.		gal.	liter	cu. ft.	cu. m.	lbs.	kilos
PJR-20S	11.4	28.9	17.5	44.4	3/4"	5.3	20	1.5	0.04	13.3	6.0
PJR-25S	12.5	31.7	17.0	43.2	3/4"	8.5	32	2.5	0.07	13.0	6.9
PJR-44S	16.3	41.4	20.8	52.8	1"	14.0	53	3.9	0.11	27.0	12.3
PJR-66S	16.3	41.4	28.5	72.4	1"	20.0	80	4.5	0.13	38.0	17.2

All Models: 28 psi/1.9 bar pre-charge
 Maximum working pressure: All models – 125psi/8.5 bar
 Maximum working temperature: All models – 140°F/60°Celsius

Quick Sizing Chart

Model #s	Total Tank Volume		Drawdown					
			@20/40		@30/50		@40/60	
	gal.	liters	gal.	liters	gal.	liters	gal.	liters
PJR-6	2.1	8	0.8	2.9	0.7	2.5	0.6	2.1
PJR-15	4.8	18	1.7	6.6	1.5	5.6	1.3	4.8
PJR-20S	5.3	20	1.9	7.3	1.6	6.2	1.4	5.4
PJR-25 (S)	8.5	32	3.1	11.7	2.6	9.8	2.3	8.7
PJR-44 (S)	14.0	53	5.1	19.3	4.3	16.4	3.8	14.2
PJR-60S	20.0	80	7.6	28.8	6.5	24.8	5.5	20.8
PJR-44IL	14.0	53	5.1	19.3	4.3	16.4	3.8	14.2



Deep Drawn Steel Dome Construction



Brass Air Stem with Corrosion-Resistant Cap

Appliance Quality Paint Finish Suitable for Outdoor Installations

High Grade Butyl Diaphragm

Stainless Steel Water Connection

Polypropylene liner water chamber



Flexcon Industries
 300 Pond Street
 Randolph, Massachusetts 02368

For More Information
 Call 1.781.986.2424
 Fax 1.781.986.2029
 www.flexconind.com