



## SMART TANK

### ST 60 . . . . . For flow rates up to 15 GPM

1" Smart Tee  
Accessory Tailpiece with 75 PSI relief Valve  
WR 60 Online 20 gallon tank

### ST 140 . . . . . For flow rates up to 30 GPM

1 1/4" Smart Tee  
Accessory Tailpiece with 75 PSI Relief Valve  
WR 140 Online 44 gallon tank

SMART TEE VALVE SPECIFICATIONS					
Model	Connections		Factory Setting	Pressure Range	Max Inlet Pressure
	Inlet & Outlet	Additional Tappings			
SMT 1" 1" tailpiece	3/4"F x 1"M 1" FTP	1" online union (2) 1/4"F & (2) 3/4" F	5 gpm @50 psi	30-75 psi	400 psi
SMT 1 1/4" 1" tailpiece	1"F x 1 1/4"M 1 1/4"FTP	1 1/4" online union (2) 1/4"F & (2) 3/4" F	10 gpm @50 psi	30-75 psi	400 psi

TANK SPECIFICATIONS							
Model #'s	Dimensions		Volume (gallons)	Drawdown (gallons)			Shipping Weight (lbs.)
	Diameter	Height		@20/40	@30/50	@40/60	
WR 60 OLC	16"	29"	20	7.4	6.2	5.4	46
WR 140 OLC	21"	36.25"	44	16.3	13.6	11.9	80

Max. Working Pressure: 100 PSI  
Factory Precharge: 28 PSI

Valve Connections: 1" FPT  
Pressure Switch Connection: 1/4" FPT

## Flow Characteristics

