

Submittal Data

Flex2Pro WWT Series

Water System Tanks

Job Name: _____

Schedule #: _____

Location: _____

Model #: _____

Engineer: _____

Representative: _____

Contractor: _____

Materials of Construction

Shell: Drawn steel w/ epoxy finish

Diaphragm: Butyl rubber w/ copolymer polypropylene lower water chamber

Connection: Stainless Steel FPT

Ratings

Max. Working Pressure (Adjustable): 325 PSI

Max. Working Temp: 140 F

Description

Flex2Pro (WWT) series tanks are diaphragm type pre-charged hydro-pneumatic tanks designed for residential and commercial water well, pressure booster, and irrigation systems.



Tank Specifications

Model	Diameter (inches)	Height (inches)	System Connection (inches)	Volume (gallons)	Drawdown (gallons)			Weight (lbs)
					20/40	30/50	40/60	
WWT 14	16	22	1	14	5.6	4.8	4.1	28
WWT 20	16	29	1	20	8.1	6.8	5.9	36
WWT 25	16	34.5	1	26	10.5	8.9	7.7	41
WWT 30	21	27.75	1 ¼	32	12.9	10.9	9.4	54
WWT 35	16	42.75	1	33.4	13.3	11.3	9.7	49
WWT 45	21	36.25	1 ¼	44	17.7	15.0	13.0	67
WWT 65	21	48	1 ¼	62	25.0	21.1	18.3	82
WWT 80	21	62	1 ¼	81	32.6	27.6	23.9	99
WWT 85	26	44.5	1 ¼	85	34.3	29.0	25.1	121
WWT 120	26	59.75	1 ¼	119	48.0	40.6	35.1	153

