

Submittal Data

Flex2Pro WWT Series

Water System Tanks

Job Name: _____ Schedule #: _____
 Location: _____ Model #: _____
 Engineer: _____ Representative: _____
 Contractor: _____

Description

Flex2Pro (WWT) Series tanks are diaphragm type pre-charged hydro-pneumatic tanks designed for residential and commercial water well, pressure booster, and irrigation systems.

Materials of Construction

Shell: Drawn Steel w/ Epoxy Finish
Diaphragm: Butyl Rubber w/cross-linked polyethylene lower water chamber.
Connection: Steel FPT

Ratings

Max. Working Pressure 125 PSI
 Max. Working Temperature 140 F
 Pre-charge (Adjustable) 38 PSI



Tank Specifications

Model	Diameter (inches)	Height (inches)	System Connection (inches)	Volume (gallons)	Drawdown (Gallons)			Weight (lbs)
					20/40	30/50	40/60	
WWT 14	16	22	1	14	5.6	4.8	4.1	28
WWT 20	16	29	1	20	8.1	6.8	5.9	36
WWT 25	16	34.5	1	26	10.5	8.9	7.7	41
WWT 30	21	27.75	1 ¼	32	12.9	10.9	9.4	54
WWT 35	16	42.75	1	33.4	13.3	11.3	9.7	49
WWT 45	21	36.25	1 ¼	44	17.7	15.0	13.0	67
WWT 65	21	48	1 ¼	62	25.0	21.1	18.3	82
WWT 80	21	62	1 ¼	81	32.6	27.6	23.9	99
WWT 85	26	44.5	1 ¼	85	34.3	29.0	25.1	121
WWT 120	26	59.75	1 ¼	119	48.0	40.6	35.1	153

